

# OUTDOOR SPOT & FLOOD LIGHTS



## WASH LIGHTS | IP65



**CHROMA 40-RGBW**

- 40x 15 Watt RGBW LEDs
- 30.000 Lumen
- 5 segments - each controllable
- IP65 classification
- eventCON® cable system



**SUPERNOVA RGBW**

- 1372 x OSRAM® LEDs
- 60.000 Lumen
- 4 segments - each controllable
- IP65 classification
- eventCON® cable system



**SUPERNOVA 896-W**

- 896 white 6.500K OSRAM® LEDs
- 80.000 Lumen
- 8 segments - each controllable
- IP65 classification
- eventCON® cable system



**NOVA 448-W**

- 448 white 6.500K OSRAM® LEDs
- 40.000 Lumen
- 4 Segments - each controllable
- IP65 classification
- eventCON® cable system

## SPOT LIGHTS | IP67 & IP65



**BABYZOOM 4**

- 4x 60 Watt OSRAM® RGBW LEDs
- 8°-50° beam angle
- IP67 classification
- eventCON® cable system
- Wireless DMX



**BABYZOOM 1**

- 1x 60 Watt OSRAM® RGBW LED
- 6°- 45° beam angle
- IP67 classification
- eventCON® cable system
- Wireless DMX



**BABYBEAM 7**

- 7 x 30 Watt RGBW Osram® LED
- 6° beam angle
- 20°, 40°, 60° and 60°x10° filter optional
- IP65 classification
- powerCON TRUE1 / 5 pol DMX
- ultra compact housing



**BABYBEAM 4**

- 4x 15 Watt RGBW OSRAM® LEDs
- 8° beam angle
- 18° & 58° diffusion filter
- IP67 classification
- eventCON® cable system
- Very compact housing



BABY**BEAM**7

# BABYBEAM 7

- » 7 X 30 WATT RGBW OSRAM® LED
- » 6° BEAM ANGLE
- » 20°, 40°, 60° AND 60°X10° DIFFUSION FILTER OPTIONAL
- » IP65 CLASSIFICATION
- » POWERCON TRUE1 / 5 POL DMX
- » ULTRA COMPACT HOUSING



## TECHNICAL DATA

### LIGHT SOURCE

- » 7 x 30 W Osram® RGBW LED
- » Lifetime LED: approx. 20.000 h

### OPTICAL SYSTEM

- » ConstantColor™ Optics
- » Beam angle 6°

### FUNCTIONS

- » High resolution dimmer 0-100%
- » Selectable dimming curves
- » Strobe with variable speed (max. 20 Hz)
- » Presets for random strobe and pulse effects
- » RGBW, 8 or 16 Bit color mixing
- » SteadyColor™ Dimming
- » Seamless CTO
- » Virtual color wheel with 39 colors including white (2700 K / 3200 K / 4200 K / 5600 K / 7200 K / 8000 K)

### CONTROLLING AND PROGRAMMING

- » Setup and addressing via OLED display with 4 buttons
- » Protocol: USITT DMX-512
- » Channels: 2,3,4,5,6,8
- » 6 DMX control modes
- » Stand-alone mode
- » 3 editable programs with up to 30 steps each
- » DMX In/Out: XLR 5 pin (IP65)
- » Power In/Out: Neutrik powerCON TRUE1

### THERMAL CONDITIONS

- » Max. environment temperature: 45° C (113° F)
- » Convection cooled

### POWER SUPPLY

- » Electronic switching power supply with auto. recognition
- » Input voltage: 100 - 240 V AC, 50 / 60 Hz
- » Max. power consumption: 220 Watt

### HARDWARE

- » IP65 protection class
- » Height with stand: 287 mm
- » Height without stand: 210 mm
- » Width: 237 mm
- » Length: 166 mm
- » Weight: 7,7 kg

### MOUNTING

- 1 x hole with 12mm diameter for one point mounting
- 1 x Omega Bracket (optional)
- 1 mount for safety wire

### INCLUDED ACCESSORIES

- » Adapter Schuko to powerCON TRUE1
- » IR Remote Control

### OPTIONAL ACCESSORIES

- » Omega Bracket
- » Diffusion filters